






BONFIX (KIWA-APPROVED) STOP COCKS WITH BALL VALVE

 STOP COCKS  SUPERIOR IN PRICE & QUALITY  KIWA-APPROVED



PRODUCT CATALOGUE

BONFIX (KIWA-approved) stop cocks with ball valve

 <p>Without drain plug 2 x compression ends</p>	 <p>With drain plug 2 x compression ends 12mm - 28mm</p>	 <p>With drain plug 2 x compression ends 35mm - 54 mm</p>	 <p>With drain plug 2 x female 1/2" - 1"</p>	 <p>With drain plug 2 x female 1 1/4" - 2"</p>
 <p>With drain plug and non-return check 2 x compression ends</p>				

INTRODUCTION

BONFIX B.V. supplies a large range of KIWA-approved stop cocks with ball valve with or without drain plug, under the BONFIX brand name.

TECHNICAL INFORMATION

The technical specifications are based on the current industry and regulatory status. BONFIX B.V. reserves the right to modify technical specifications without prior notice. No rights can be derived from the technical information provided in this brochure.



GENERAL

BONFIX stop cocks with ball valve are designed for shutting of the water supply by way of a ball valve. The stop cocks are dimensioned for full flow capacity and are provided with an easy action, blue lever with clearly visible open / shut positions. Thanks to maximized valve action the flow rate in the water system is not impaired.

PRODUCT USAGE

BONFIX stop cocks with ball valve are designed for use in drinking water systems and central heating systems. The compression fittings offer specific advantages with renovation projects, enabling quick and easy installation in places where access is impaired. Other forms of usage, depending on pressure/temperature and medium, may be permitted but require prior written approval by BONFIX B.V.

TECHNICAL SPECIFICATIONS

BONFIX stop cocks with ball valve are made from premium quality brass (CuZn40Pb2) and provided with a chrome-plated ball with Teflon sealing to ensure permanent easy and light operation. The models with a drain facility come fully fitted with a G1/4" plug on one side only. BONFIX stop cocks with ball valve are designed for use in water supply systems with a working pressure not exceeding 1000 kPa (10 bar) and temperatures not exceeding +90 °C.


QUALITY MARK

BONFIX stop cocks with ball valve bear the KIWA quality mark.

INSTALLATION INSTRUCTIONS

For the installation of a BONFIX stop cock with ball valve, refer to the technical documentation of compression fittings.

Other forms of usage, depending on pressure/ temperature and medium, may be permitted but require prior written endorsement from BONFIX B.V.

 Use appropriate tools for installation and prevent damage.

WARRANTY AND LIABILITY

Warranty and liability apply as per our general terms and conditions.
Damage caused by stress corrosion is not covered under product warranty.

bonfix® *Superieur*

 **SUPERIOR IN PRICE & QUALITY**



LIKE BONFIX ON FACEBOOK

- ✓ Always up to date on new products
- ✓ Fun actions and specials
- ✓ Direct contact with BONFIX staff OR
- ✓ Visit our website: www.bonfix.eu